




Vacuum Depanner Belts



Vacuum Depanner Belts

Vacuum depanner belts are three ply fabric backed, with a white FDA food grade PVC coated front (bread facing side). The belt is 5mm thick and joined with a supplier finger over finger spliced bi-directional join. The belt can operate in temperatures up to 110°C, are long lasting, chemical resistant, strong and durable. Belts are usually supplied pre-loaded with the


appropriate cups and retainers to suit the customers specification but can also be supplied blank.

BST supply a wide range of detectable retaining clips to achieve varying reach of airflow, as well as a wide range of detectable cups to achieve levels of flex and optimum suction on the product.

Cleaning Advice

Industrial Methylated Spirits is used to wipe clean the belts before fitting the cups. However, many food manufacturers tend to use alkaline foaming agents which are acceptable if the concentrations are not too high.

We recommend that you clean your depanner belts in the same manner as any other standard fabric reinforced conveyor belts.



The information provided in this product specification sheet is based on our experience and knowledge to date and we believe it to be true and reliable. This information is intended as a guide for your use of our products, the use of which is entirely at your own discretion and risk. We, BS Teasdale & Son Ltd, cannot guarantee favourable results and assume no liability in connection with the use of our products. © 2023 BS Teasdale & Son Ltd. All Content, Data & Images are owned by BS Teasdale & Son Ltd and are protected by international copyright law.

BS Teasdale & Son Ltd. Unit 7, Delta Court, Sky Business Park, Doncaster, South Yorkshire, DN9 3GN

Tel: +44(0)1302 775208 **Email:** sales@bst-detectable.com **Web:** www.bst-detectable.com